



Specification

Model No.:	RS-UW18W316X(88105) / RS-UW24W316X(88105)
Front cover & Housing:	Stainless steel 316L
Dimensions:	D123*H165mm(Max.)
Tempered Glass:	8mm thickness
LED chip:	CREE / EDISON
LED Q'ty:	6pcs 3W LED / 6pcs 3in1 LED / 6pcs 4in1 LED
Cable gland:	Stainless steel 316L PG13.5
Driver:	Constant current driver
Lens:	Clear, Bead, Frosted
Beam Angle Options:	10° 20° 30° 45° 60° 90°
Power Cable:	AWG 5/18 or AWG 3/18 SOW rubber cable
Protection Class:	IP68
Environment:	Dry / Submerged
Mounting Hardware:	Surface Mounted System
Net Weight:	2kgs with 1.5m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88105.063.01	2700-3000K	6*3	V+/V-	AC/DC12-24	1500 / 750	18	840
88105.063.02	4000-4500K	6*3	V+/V-	AC/DC12-24	1500 / 750	18	888
88105.063.03	5000-5500K	6*3	V+/V-	AC/DC12-24	1500 / 750	18	930
88105.063.04	6000-6500K	6*3	V+/V-	AC/DC12-24	1500 / 750	18	930
88105.063.05	Red	6*3	V+/V-	AC/DC12-24	1000 / 500	12	210
88105.063.06	Green	6*3	V+/V-	AC/DC12-24	1500 / 750	18	540
88105.063.07	Blue	6*3	V+/V-	AC/DC12-24	1500 / 750	18	240
88105.063.08	Yellow	6*3	V+/V-	AC/DC12-24	1500 / 750	18	570
88105.063.09	RGB-DMX512 (3 channel)	6*3	V+ /V-/D+/D-/GND	AC/DC12-24	R: 333 / 166 B: 500 / 250 G: 500 / 250	R: 4 B: 6 G: 6	R: 70 B: 80 G: 180
88105.063.10	RGB-DMX512 (3 channel)	6*3in1	V+ /V-/D+/D-/GND	AC/DC12-24	R: 500 / 250 B: 500 / 250 G: 500 / 250	R: 6 B: 6 G: 6	R: 150 B: 180 G: 360
88105.063.11	Auto changing color	6*3	V+/V-	AC12-24	R: 333 / 166 B: 500 / 250 G: 500 / 250	R: 4 B: 6 G: 6	R: 70 B: 80 G: 180
88105.063.13	RGBV+ (build-in CC driver)	6*3	R/G/B/V+	DC12-24	R: 333 / 166 B: 500 / 250 G: 500 / 250	R: 4 B: 6 G: 6	R: 70 B: 80 G: 180
88105.064.14	RGBW-DMX512 (4 channel)	6*4in1	V+ /V-/D+/D-/GND	DC24	R: 250 B: 250 G: 250 W: 250	R: 6 B: 6 G: 6 W: 6	R: 150 B: 180 G: 360 W: 540

