



## Specification

<b>Model No.:</b>	RS-LS9W(88424)
<b>Front cover &amp; Housing:</b>	Aluminum body
<b>Dimensions:</b>	D138*H181mm
<b>Tempered Glass:</b>	8mm thickness
<b>LED chip:</b>	Epistar
<b>LED Q'ty:</b>	9pcs 1W LED
<b>Cable gland:</b>	Nickel plated brass PG9
<b>Driver:</b>	Constant current driver
<b>Lens:</b>	Clear, Bead, Frosted
<b>Beam Angle Options:</b>	10° 30° 45° 60° 90°
<b>Power Cable:</b>	2*1.0mm <sup>2</sup> / 3*0.75mm <sup>2</sup> / 4*0.75mm <sup>2</sup> / 2*1.0mm <sup>2</sup> +3*0.75mm <sup>2</sup> VDE rubber cable
<b>Protection Class:</b>	IP65
<b>Environment:</b>	Dry
<b>Mounting Hardware:</b>	Wall, ceiling, floor, pole mounting
<b>Net Weight:</b>	1kgs with 1m cable
<b>Lifetime:</b>	>50000H

## Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88424.091.01	2700-3000K	9*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	810
88424.091.02	4000-4500K	9*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	855
88424.091.03	5000-5500K	9*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	900
88424.091.04	6000-6500K	9*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	900
88424.091.05	Red	9*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	225
88424.091.06	Green	9*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	540
88424.091.07	Blue	9*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	270
88424.091.08	Yellow	9*1	V+/V- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	630
88424.091.09	RGB-DMX512 (3 channel)	9*1	V+/V- /D+/D-/GND	AC/DC12	R: 250 B: 250 G: 250	R: 3 B: 3 G: 3	R: 75 B: 90 G: 180
88424.091.10	Auto changing color	9*1	V+/V-	AC12	R: 250 B: 250 G: 250	R: 3 B: 3 G: 3	R: 75 B: 90 G: 180
88424.091.12	RGBV+ (build-in CC driver)	9*1	R/G/B/V+	DC12	R: 250 B: 250 G: 250	R: 3 B: 3 G: 3	R: 75 B: 90 G: 180

